



May 6, 2002

DN-6910 • J-200

SSM Series Alarm Bells

Section: Audio/Visual Appliances

GENERAL

System Sensor's **SSM Series** alarm bells are low-current, high-decibel notification appliances for use in fire and burglary systems or other signaling applications. They come pre-wired to reduce installation time, and also incorporate a polarized electrical design for use with supervision circuitry.

Reliable performance. SSM Series alarm bells provide loud, resonant tones. They operate on 24 VDC and are motor-driven.

Simplified installation. For indoor use, SSM Series alarm bells mount to a standard 4" (10.16 cm) square electrical box. For outdoor applications, a **WBB** weatherproof backbox is used.

FEATURES

- Approved for indoor or outdoor (with WBB backbox) use.
- Low current draw.
- High dB output.
- Three sizes available: 6" (15.24 cm), 8" (20.32 cm), and 10" (25.40 cm) diameter.
- 24 VDC models; polarized for use with supervision circuitry.
- Bells mount directly to standard 4" (10.16 cm) square electrical box.

SPECIFICATIONS

Nominal voltage: 24 VDC.

Operating voltage range: 19.2 to 26.4 VDC.

Average current draw: 0.03 A.

Sound output: 85 dB.

Operating temperature range: -31°F (-35°C) to +140°F (+60°C).

Termination: provided with two sets of leads for in/out wiring.

Service use: Fire Alarm, General Signaling, Burglar Alarm.

ENGINEERING AND ARCHITECTURAL SPECIFICATIONS

Model shall be a SSM Series alarm bell. Bells shall have underdome strikers and operating mechanisms. Gongs on said bell shall be no smaller than nominal 6" (15.24 cm), 8" (20.32 cm), or 10" (25.40 cm) (*specify size*) with an operating voltage of 24 VDC. Bells shall be suitable for surface or semi-flush mounting. Outdoor surface-mounted installations shall be weatherproof (using optional WBB weatherproof backbox); otherwise, bells shall mount to a standard 4" (10.16 cm) square electrical box having a minimum projection of 2.5" (6.35 cm). Bells shall be located as shown on the installation drawings or as determined by the Authority Having Jurisdiction. Bells shall be Listed for indoor/outdoor use by Underwriters Laboratories, ULC (Canada), and the California State Fire Marshal, and approved by Factory Mutual and MEA.



LISTED
S4011



CS548, Vol. 7
(SSM24-6A,
SSM24-8A,
SSM24-10A)



California
State Fire
Marshal

7135-1209:164



331-01-E



Approved



6910pho1.jpg

ORDERING INFORMATION

- SSM24-6** 6" (15.24 cm) bell, 24 VDC, polarized, 85 dBA.
- SSM24-6A** Canadian model of 6" bell above.
- SSM24-8** 8" (20.32 cm) bell, 24 VDC, polarized, 85 dBA.
- SSM24-8A** Canadian model of 8" bell above.
- SSM24-10** 10" (25.40 cm) bell, 24 VDC, polarized, 85 dBA.
- SSM24-10A** Canadian model of 10" above.
- WBB** Weatherproof backbox.

NOTIFIER® is an operation of **Honeywell**.

This document is not intended to be used for installation purposes. We try to keep our product information up-to-date and accurate. We cannot cover all specific applications or anticipate all requirements. All specifications are subject to change without notice. For more information, contact **NOTIFIER**. Phone: (203) 484-7161 FAX: (203) 484-7118



NOTIFIER®

12 Clintonville Road, Northford, Connecticut 06472

ISO 9001
CERTIFIED
ENGINEERING & MANUFACTURING